




Side Seal 520

Vertical Form Fill & Seal

For 3 & 4 Side Seal Bags with Zipper Option

Up to 50 packages
per minute

Bag Styles



Optional Fillers



Ancillary Equip



Maximum Speed:

Up to 50 Bags/Min

Minimum Bag Size:

95mm(W) x 50mm(L)
3.74" (W) x 1.97" (L)

Maximum Bag Size:

260mm(W) x 350mm(L)
10.24" (W) x 13.78" (L)

Maximum Web Width:

190mm - 520mm | 7.48"-20.47"

Film Thickness:

0.04mm - 0.09mm

Standard Electrical:

220v/20amp Single Phase/3 Phase
Depending on Options

Equipment Dimension's:

1400mm x 1260mm x 1680mm
55.1" (L) x 49.6" (W) x 66.1 (H)

Weight: 600Kg | 1323Lbs



The Advanced technology process control system of the **SS520** offers a multi-functional programmable system with various alarm systems to reduce waste and down time. The **SS520** features a large **color** touch screen with anti-glare panel. An automatic film rectifying alignment system is on board with electric photo eye film registration. The film draw down system is controlled with dual servo motors. The **SS520** runs most common film structures and has an auto stop end of film lock down device. An advanced adjustable edge seal device is on board with Siemens control platform and components. Smooth air actuation drive seal jaws and a VFD powered film unwind for high accuracy. Easy access to off the shelf components on most wear parts makes for easy operations with minimal maintenance. A quick change film splice table is also on board.

OPTIONS

- Ethernet remote diagnostics
- Zipper applicator device
- Gas flush assembly
- Chain bag repeat program
- Round/Euro hole punch
- Tear notch device
- Static eliminator device
- Vacuum pull belts and pump
- Load shelf assembly
- In-feed and exit conveyors
- Integration with variety of fillers, weighers, printers, and metal detectors.



4760 Young Deer Drive
Cumming, GA 30041
770-888-4512 phone

www.innovativeps.com